AC18Pro IP Camera Manual

[Part 1: Connect and manage cameras using mobile APP]


All software and Manual download weblink: http://www.yucvision.com/AC18PRO-Download.html

Please go google play or Apple store download mobile APP, the name is AC18Pro and install it into your mobile phone The first time you run the APP, you need to register an account. You can use your email or mobile phone number to register an account, and then use the registered account to log in to the APP.


[1], Configure the camera using WIFI

1. If your camera has WIFI function. Before connecting the power adapter of the camera, please make sure that the LAN port of the camera is not connected to the Ethernet cable (if you have connected it, please disconnect it and press the reset button for 5 seconds to restore the camera to factory settings). After connecting the power, wait 10 seconds.

Before using the mobile APP to configure the camera, please connect your mobile phone to your WIFI router via WIFI.
Open the APP and click the Add button to add a camera (as shown in Figure 1). And select WIFI (as shown in Figure2), the software will automatically obtain the WIFI of the mobile phone, and please enter the WIFI password (the WIFI connection password of the wireless router). Click Next (as shown in Figure 3)




After entering the interface of Figure 4, wait for a few seconds, the APP will automatically enter the interface of Figure 5, and the camera will start to match the code through sound waves. When you hear a "di" on the phone, it means that the camera is successfully connected to your wireless router via WIFI (as shown in Figure 6). If your camera does not have a microphone and a speaker at the same time, the sound wave code matching cannot be completed, but you can also add the camera after aligning the QR code on the phone screen with the camera lens. Click the camera on Figure 7, and you will enter the camera's monitoring and management interface (as shown in Figure 8). The camera has been added successfully.




[2], Add a camera by scanning a QR code

If your camera does not have WIFI function, please connect the ethernet cable to your switch/router and connect the power adapter. Select "Wired connection camera", as shown in Figure 9, enter the interface of scanning the QR code to add a camera, point the mobile phone at the QR code on the camera body to scan (as shown in Figure 10), after scanning is successful, please provide your Customize a name for the camera, and click "BIND IT" to complete the addition (as shown in Figure 12)




[3], Add cameras via LAN connection

If the QR code cannot be found on the camera, you can click "Click here to add a device" to add the camera through the LAN search (as shown in Figure 12), enter the search page, and the APP will automatically search for the camera, as shown in Figure 13 display, and then click the camera to complete the addition.



[4], How to Turn on/off auto humanoid Tracking



1,Control the PTZ button to rotate the camera to your desired position (set a Return position) 2. Switch the PTZ control interface to "SENIOR" setting interface.

3, Input 88, Then click "Add" button. The tracking return position (Home position) set successfully

4,Click "Start Track" button, The camera will automatically turn on the tracking function

5, Click "Stop Track" button, the camera will automatically turn off the tracking function

Part 2: Add and manage cameras using PC software

[1],Install search tool on your PC




3

2, Run the software, as shown below (4)

All MetCard All MetCards 🗸 Start Search Export to Excel 🕑 QR code 🗌 Audio 🕑 Full screen switching stree						Total:1	Total:1 Seleted:0		A DEVICE TOOLS FOR SEARCHING/CONFIGURING/UPGRADDING V5.1.9_20201215							- n ×			
Address	HTTP M	odel	Title Nume	Firmware	Version.		Status		All subn	53.	All Het	Card All NetCards	~ (Start Search Amport to	Excel 🔄 QR code 🗌	Andio 🕝 Pull sore	en seitching stre	, Total	l:1 Sele
192.168.1.59	80 1	08005	Canera	MC8005_A	V2_STARC-RTMP-H5	3.0.6.4 build	00:32:15 Alarm:video	Maman shape detect	ed. close	2700000	IP Address	HTTP Nodel	Title Hane	Fireware Version		Status			n SH
											192, 163, 1, 59	80 \$20005	Goto Web	HOROGE AN UNICTARCERTNE-HS	V3.0.6.4 build	00:35:10 Alers:vides	Human shape dete	oted. close	E
										_			Remote config						
													Video window						
										-			Video window One-click play	,					
													Only Play Audio						
													Stop playing						
										-			Reboot IPC						
													Modify IP address						
													Alloc available IP addr	esses					
										_			Factory setting						
													Snap picture						
													Open snap directory						
													P2P ID UPLOAD	>					
													ISP BIN upload	>					
													ONVIE	>					
										_			HIK	>					
													DH TST	>					
Batch Reset	Batch Babo		Setting	tch Set video d audio encode	All submet ONVIF	Batch Timing Maintenance	Video window	print label						,					
patch heset	Datch Depo	AL Dates	ab ab	d audio encoda	ALL SUBAT ONLY	Maintenance	11040 AIP00A				Batch Reset	Batch Esboot	IMPORT XML EXPORT XML	subnet CSVII	Batch Tining Maintenance	Video vindov	print label		
Upgrade Firmware E:\安佳\新界面-台湾\MCSOOL-LS\firmware_MCSOOLS_VO_AF		VO_AF Browse	Batch Sync Time	Batch Set Password	Batch Set Language	Batch Sat Flatform		Conv OR	Upgrade E:	、安佳、新界面-台湾(MD50)	COPY XML	h Sync Tine	Batch Set Panyerd	Batch Set Language	Batch Set Flatform		1-		
Upgrade firmware by C:\Users\Fublic\Documents		Browse		Ratch Snan			2981 N	Code		On the survey of the state of t	BATCH ADD			Language	ristfors	문양문문	Copy		
firnvare by C:\Users\Public\Documents			50HZ/60HZ	Batch Snap Picture	Control IO Output	Audio	228665 -		Ermeare by C: path	\Wsers\Public\Document:	Default User Setting	OHZ/60HZ	Batch Snap Fisture	Control IO Output	Audio	122223			
Upload				Browse	Batch Download Config	Batch Set Title	Batch Motion Detection	Factory Mode	DOM:	Print QR Code			Copy SN	A Dowlard		Presile Monton		16/997	Print
JOREIG					Centig		peteotion				Upload		CopyUUID	th Bownload Config	Batoh Set Title	Batch Motion Detection	Factory Mode	TELESON & S	1


3, Here you can modify the IP address of the camera, upgrade the firmware and other parameter settings. Right-click on the IP address to open the camera with a browser, as shown in the figure 5.

4,Enter the browser login interface, login user name: admin, password: 123456, as shown in the following figure (if the browser prompts you to download and install the plug-in, please download and install it): Then click login, as shown in the figure 7



[2],Use PC software to search and add cameras

1, Install the LMS computer software.




安装语言		×
	请选择你要安装的语言	
	English	~
	ОК	Cancel
	9	

The software supports English, Simplified Chinese and Traditional Chinese (if you want to support other languages, we can provide you with language packs, you can translate into the language you want, and then we can provide you with software customization)

- 2, Follow the prompts to complete the software installation
- 3, Run the LMS software:user:admin,password:123456



Click LOGIN to log in to the software





11

4. Search and add cameras.Click "Devices>""Start Search">click"3">add >successfully added, as shown in the figure 10

Then click" go to Liveview, as shown in the figure 11

Double click on the IP address and the video will automatically appear in the video box on the right.

[3], Preview and control cameras with AC18PRO PC software

1, Double-click the AC18PRO software in the directory, follow the prompts to complete the installation of the camera, and then run the camera. Manual

AC18Pro_install_V1.0.0_20220408.exe
科 AjDevTools_V5.1.9_20201215.exe
MS_install_V5.0.5_20211123.exe

2, run and login AC18PRO,

The username and password here are the account you registered for the first time on your mobile phone.

Click login button go to AC18PRO

You will see all the cameras under your account, you can preview the

cameras and view the video playback in this way



Part 2: Camera PTZ Control Command List

Function name	Explanation	Preset	Call	Set
Set return position	position of the camera return after the end of the tracking(set a tracking home position)	88		\checkmark
Turn On auto tracking	Turn On auto tracking (It is not recommended to turn on the tracking function for a long time.)	97	V	
Turn OFF auto tracking	Turn off auto tracking (default)	96	\checkmark	
Set and open the Home position	Rotate the camera to the position you want, then Set 1th preset, and the 1th preset position is the Home position, When the camera is in standby, the camera will automatically rotate to 1th preset position 76+set+1+call Turn on Home position; 76+set+2+call for Turn off home position	76	\checkmark	
Turn On the ZOOM display	75+set	75		
Turn Off the ZOOM display	75+call	75	\checkmark	
Restart PT speed	Restart only PT Speed dome (94+call)	94		\checkmark
Reset PT Speed	Reset only PT rotation control information to factory settings(82+call)	82	\checkmark	